



My Account Checkout Login/Logout Help

Search by keyword #

Search

0 item(s)
Total: \$0.00

LIVE CHAT
Click Here to Chat

HOME RECONDITIONED EQUIPMENT NEW EQUIPMENT CLEANING CHEMICALS CONTACT US

Rider Floor Scrubbers Walk Behind Floor Scrubbers Rider Sweepers Walk Behind Sweepers Trade in Equipment Leasing

Reconditioned Equipment

- Floor Scrubbers
- Industrial Sweepers
- Sweeper Scrubbers

New Equipment

- Tennant
- Viper

Rentals

- Floor Scrubber Rentals
- Sweeper Rentals

Cleaning Chemicals

- Soaps
- Degreasers
- Freezer Cleaners

Parts

- Parts
- Batteries
- Brushes / Brooms
- Squeegee's
- Battery Chargers

Services

- Warehouse Cleaning
- Service & Repairs



Home > Industrial Sweepers >

Reconditioned Tennant 385 rider sweeper



Reconditioned Tennant 385 rider sweeper

LARGER PHOTO

EMAIL A FRIEND

Like 0

Reconditioned Tennant 385 rider sweeper (enclosed cab)
Our Price: \$15,849.00

1

ADD TO CART

\$437 / mo

Email me when Back-In-Stock

Product Code: TENNANT 385

Description

The Tennant 385 industrial rider Sweeper was designed on Tennant's standard mid-sized frame. With larger hydraulic components than previous models, the Tennant 385 powers up steep inclines even when the hopper is full. The 385 uses a reliable hydrostaic drive, and dumps into a standard sized dumpster. Unit is available with or without enclosed cab.

Unit Includes:

- Rebuilt Ford 4 cyl. motor
- Enclosed cab
- New Brooms
- New Flaps
- New Filters
- New Paint Decals
- 90 days parts warranty
- Fully Serviced and Reliable

Tennant 385 Specs:

SPECIFICATIONS GENERAL MACHINE DIMENSIONS/CAPACITIES

- Item Dimension/capacity Length 2360 mm (93 in)
- Width 1590 mm (62.5 in)
- Height 1475 mm (58 in)
- Height with overhead guard 2080 mm (82 in)
- Height with overhead guard and hazard light 2270 mm (89.5 in)
- Height with cab 2100 mm (82.62 in)
- Height with cab and hazard light 2285 mm (90 in)
- Track 1345 mm (53 in) Wheelbase 1135 mm (44.75 in)
- Main brush diameter 355 mm (14 in)
- Main brush length 1145 mm (45 in)
- Side brush diameter 585 mm (23 in)
- Sweeping path width 1145 mm (45 in)
- Sweeping path width with side brush 1525 mm (60 in)
- Main brush pattern width 50 to 65 mm (2.0 to 2.5 in)
- Hopper weight capacity 545 kg (1200 lb)
- Hopper volume capacity 396 L (14 cu ft)
- Dust filter area 6.9 m² (74 sq ft) GVWR 1927 kg (4250 lb)
- Sound level 80 dBA Ceiling height minimum dumping clearance 2745 mm (9 ft)

GENERAL MACHINE PERFORMANCE

- Item Measure Maximum forward speed 13.7 kmh (8.5 mph)
- Maximum reverse speed 4.0 kmh (2.5 mph)
- Minimum aisle turn width, left 2870 mm (113 in)
- Minimum aisle turn width, right 4725 mm (186 in)
- Maximum rated climb and descent angle 6_ SPECIFICATIONS 355 MM300 (3--97) 83

POWER TYPE

- Engine Type Ignition Cycle Aspiration Cylinders Bore Stroke Ford VSG 1.1L Piston Distributorlesstype spark 4 Natural 4 69 mm (2.70 in) 76 mm (2.97 in)

COUPONS

COUPONS FOR SWEEPERS & FLOOR SCRUBBERS

Rent any Sweeper or Floor Scrubber for 2 days, and get the 3rd Day FREE!

Applies to any of our Sweeper or Floor Scrubber Rental equipment



TRADE IN & SAVE

Displacement Net power, governed Net power, maximum 1100 cc (67 cu in) 20.3 kw (28 hp) @ 2400 rpm 32.8 kw (44 hp) @ 3600 rpm Ford VSG 1.3L
 Piston Distributorless type spark 4 Natural 4 74 mm (2.91 in) 75 mm (2.97 in)
Displacement
 Net power, governed Net power, maximum 1300 cc (79 cu in) 23.2 kw (32 hp) @ 2400 rpm 39.5 kw (53 hp) @ 4000 rpm Ford VSG 1 1L d 1 3L
 Fuel Cooling system Electrical system 1.1L and 1.3L Gasoline, 87 octane minimum, unleaded.
 Fuel tank: 36 L (9.6 gal)
 Water/ethylene glycol antifreeze 12 V nominal LPG, F l t k 15 k (33 lb) Total: 4.5 L (1.2 gal) 37 A alternator
 Fuel tank: kg Radiator: 3.8 L (1 gal) Idle speed, no load (Fast 1) governed speed, under load (Fast 2)
 governed speed, under load 1350 + 250 rpm 2000 + 50 rpm 2400 + 50 rpm Spark plug gap
 Firing order Valve clearance, cold 1 mm (0.039 in) 1--2--4--3, counterclockwise rotation 0.22 mm (0.009 in) intake 0.32 mm (0.013 in) exhaust
 Engine lubricating oil with filter 3.3 L (3.5 qt) 10W--30 SAE--SG/SH
SPECIFICATIONS 84 355 MM300 (3--97)
STEERING
 Type Power source Emergency steering Rear wheel, hydraulic cylinder and rotary valve controlled Hydraulic accessory pump Manual
HYDRAULIC SYSTEM
 System Capacity Fluid Type Hydraulic reservoir 24.6 L (6.5 gal)
 TENNANT part no. 65869 -- above 7_C (45_F)
 Hydraulic total N/A L (N/A gal) p) TENNANT part no. 65870 -- below 7_C (45_F)
BRAKING SYSTEM
 Type Operation Service brakes Mechanical drum brakes (2), one per front wheel, cable actuated Parking brake Utilize service brakes, cable actuated TIRES Location Type Size Pressure Front (2) Solid 5 x 18 in -- Rear (1) Pneumatic 6 x 19 in 790 + 35 kPa (115 + 5 psi)



Share your knowledge of this product with other customers... [Be the first to write a review](#)

Browse for more products in the same category as this item:
 Industrial Sweepers

NEWSLETTER SUBSCRIBE

Enter Your Email Address To Sign Up For Our Newsletter

Enter your email...

SUBMIT



COMPANY

- About Us
- Terms of Sale / Returns
- Privacy & Security
- Legal Statement

PRODUCTS

- FAQ's
- Product Index
- Category Index

MY ACCOUNT

- Track My Order
- My Account
- Shopping Cart

CUSTOMER SERVICE

- Contact Us
- Site Help
- Become an Affiliate

CONTACT US

323 - 400 - 5731

Copyright © 2014 SweepersAndFloorScrubbers.com. All Rights Reserved. | Built with Volusion

