



Turbo Levo Expert

The all-new Levo delivers the unbelievable power to ride more trails through an unequalled combination of ride quality, usable power, and ride anywhere range. It's the distillation, application, and amplification of a 40-year obsession with creating the world's best riding mountain bikes. Since its introduction, Levo has set the bar every other e-MTB aims for, and the new Levo raises that bar again.

It starts with our Turbo Full Power 2.2 motor and MasterMind Turbo Control Unit (TCU), which provide Levo with a smooth and seamless amplification of your efforts—4x your power that lets you choose where to ride, and when you want to do it. Levo also shatters limitations when it comes to range, amplifying your effort for up to five hours of trail time. Now you can ride farther, and explore more, than ever before. And the optimized chassis boasts 150mm of custom-tuned rear suspension and adjustable geometry that delivers a stable and natural ride like no other. Because at the end of the day, it's the ride that matters. Believe it.

Here's where the gloves come off—the Levo Expert brings it with SRAM's robust X01 Eagle 12-speed drivetrain, dialed-in FOX Performance Elite suspension, and a high-performing Roval Traverse wheelset.

- Levo's fully integrated Turbo Full Power 2.2 motor, 700Wh battery, and advanced MasterMind Turbo Control Unit deliver category-leading 90 Nm of torque and 565 watts of power for up to five hours of ride time, empowering you to ride farther and faster than ever before.
- The MasterMind Turbo Control Unit is your information hub with customizable display fields, including the exact percentage of battery level, and it features our all-new MicroTune function to adjust power delivery in 10% increments, so you get exactly the support you need to experience precisely the ride you want.
- A dedicated mixed-wheel size design with a 27.5" wheel in the back and 29" up front delivers a nimble ride that carves circles around other full-power e-MTBs. A generous cockpit centers you on the bike, optimizing traction and corner control. The low bottom bracket, slack headtube angle and reduced fork offset keep things stable in the rough.
- Levo offers six distinct geometry settings, allowing you to easily dial-in its performance for any riding style and any terrain. Head tube angle can be adjusted between 63- and 65.5-degrees. Bottom bracket height can be fine-tuned up or down by 7mm.
- Levo's 150mm of rear travel is supple on small bumps, devours square-edged hits without a twitch, eats massive G-outs for breakfast, yet still offers amazing pedal response and delivers your power to the ground with total efficiency.
- The Levo's S-Sizing is based on what matters—rider size and style, not inseam. Six sizes, all with similar headtube lengths and standover, allow you to choose the size that best suits your individual style. Smaller S-Size numbers are going to be nimble and more flickable, while bigger S-Sizes deliver more stability and a roomier ride.





Technical Specifications

COCKPIT

Stem Alloy Trail Stem, 35mm bar bore

Handlebars Specialized Trail, 7050 alloy, 8-degree backsweep, 6-degree upsweep, 30mm rise, 800mm, 35mm clamp

Grips Deity, Knuckleduster, Black

Saddle Bridge Comp, Hollow Cr-mo rails, 155/143mm

SeatPost X-Fusion Manic, infinite adjustable, two-bolt head, bottom mount cable routing, remote SLR LE lever, 34.9, S1: 100mm, S2: 125mm, S3: 150mm, S4/S5: 175mm, S6: 190mm

BRAKES

Front Brake SRAM Code RS, 4-piston caliper, hydraulic disc, S/M: 200mm, L/XL: 220mm

Rear Brake SRAM Code RS, 4-piston caliper, hydraulic disc, 200mm

DRIVETRAIN

Rear Derailleur Sram X01 Eagle, 12-speed

Shift Levers SRAM X01 Eagle trigger, 12-speed, single click

Cassette SRAM XG-1275, 12-speed, 10-52t

Chain SRAM GX Eagle, 12-speed

Crankset Praxis forged M30, custom offset, 160mm

Chainrings SRAM X-Sync Eagle, 104 BCD, 32T, steel

WHEELS

Inner Tubes Standard, Presta Valve

Front Wheel Traverse 29

Rear Wheel Traverse 27.5

Front Tire Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.6"

Rear Tire Eliminator, GRID TRAIL casing, GRIPTON® T7 compound, 2Bliss Ready, 27.5x2.6"

FRAMESET

Seat Binder Alloy, 38.6mm

Frame FACT 11m full carbon, 29" front wheel, 27.5" rear wheel, full internal cable routing, 148mm spacing, fully sealed cartridge bearings, 150mm of travel, geo adjust head tube, geo adjust horst pivot

Fork FOX FLOAT 38 Performance Elite 29, Grip2 damper, 44mm offset, HSC, LSC, HSR, LSR, 110x15mm, 1.5" tapered steerer, 160mm travel

E-BIKE

Motor Specialized Turbo Full Power System 2.2 Motor

Charger Custom charger, 42V4A w/ Rosenberger plug

UI/Remote Specialized MasterMind TCU, 10-LED State of charge, 3-LED Ride Mode display, ANT+/Bluetooth®, w/Handlebar remote

Battery Specialized M3-700, Integrated battery, 700Wh

Wiring Harness Custom Specialized wiring harness

SUSPENSION

Rear Shock FOX FLOAT X2 Performance Elite, LSC, LSR, 2-position lever, 55x210mm